



IR ENERGY INC.
 563 BARTON STREET
 STONEY CREEK, ON L8E 5S1
 PHONE: (905) 664-9082
 www.irenergy.ca

SELECT DESIRED GAS:




NATURAL GAS

SELECT DESIRED FINISH:


MARINE GRADE ALUMINUM REFLECTORS, BURNER END CAP, SERVICE COVER AND EXHAUST END CAP

BLACK CANOPY REFLECTORS. BLACK, BURNER END CAP, SERVICE COVER AND EXHAUST END CAP

316 MARINE GRADE STAINLESS REFLECTORS, BURNER AND EXHAUST END CAP, SERVICE COVER



PLAN VIEW




FRONT ELEVATION

TECHNICAL SPECIFICATIONS:


- 316 MARINE GRADE ALUMINUM AND SS BURNER HEAD CONSTRUCTION
- ALUMINUM DECORATIVE GRILLE
- GAS SUPPLY PRESSURE:
 NG INLET 14" W.C (MAX), 5" W.C (MIN)
 NG MANIFOLD 3.3" W.C.(HI), 2.0" W.C.(LOW)
- INLET CONNECTION: 1/2" FEMALE NPT.
- ELECTRIC SUPPLY: 120 VAC, 60 HZ, 1 AMP; 36" CORD WITH GROUNDED 3 PRONG PLUG.
- CONTROL: TWO-STAGE SWITCH - PART #EE020 (OPTIONAL).

WARRANTY:

- BURNER AND CONTROLS: 3 YEARS
- HEAT TREATED ALUMINIZED TUBE: 10 YEARS



STANDARD




45° TILT

CLEARANCE TO COMBUSTIBLES		
REFLECTOR CONFIGURATION	DIMENSION	MODEL NO.
		ETS50 - 9' 35,000/50,000 BTU/HR
STANDARD	A	5.5"
	B	25"
	C	66"
	D	25"
45° TILT	A	8"
	B	3"
	C	50"
	D	40"
BURNER END		4"
EXHAUST END		6"

NOTES:

1. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.
2. DO NOT SCALE DRAWING.
3. THIS DRAWING IS INTENDED FOR USE BY ARCHITECTS, ENGINEERS, CONTRACTORS, CONSULTANTS AND DESIGN PROFESSIONALS FOR PLANNING PURPOSES ONLY.
4. ALL INFORMATION CONTAINED HEREIN WAS CURRENT AT THE TIME OF DEVELOPMENT BUT MUST BE REVIEWED AND APPROVED BY THE PRODUCT MANUFACTURER TO BE CONSIDERED ACCURATE.
5. CONTRACTOR'S NOTE: FOR PRODUCT AND COMPANY INFORMATION VISIT www.CADdetails.com/info AND ENTER REFERENCE NUMBER 5029-015.



EVENTUBE

EVENTUBE HIGH OUTPUT SLIM LINE: MODEL ETS50 - 35,000BTU/HR (LO), 50,000BTU/HR (HI), 9FT. FOR NG ONLY